

## MATERIAL SAFETY DATA SHEET

Revision date : MSDS No. : 1/1/2015 M1203

General Overview			
Product Name	MXP High Performance Fully Synthetic Engine Oil		
Product Grade	5W-30 5W-40		
Physical State	Liquid		
Colour	Amber		
Odour	Mild petroleum odour		
Caution	Hot oil can cause thermal burns on contact Used motor oil has been associated with skin cancer in laboratory animals following extended contacts Spills may create spilling hazards.		
	Hazard Rankings Protective Equipment		
	HMIS       NFPA         Health       1       0         Fire Hazard       1       1         Reactivity       0       0         * = Chronic Health Hazard       Minimum Recommended See Section 8 for Details		
Section 1	Identification		
Product Name	MXP High Performance Fully Synthetic Engine Oil		
Product Code	U22346MXP U11066MXP		
Product Type	Synthetic Motor Oil		
UN Number	Not regulated		
CAS Number	None (mixture)		
Supplier	Bardahl Asia Pacific Pte Ltd 33 Ubi Avenue 3 #07-51 Vertex		
Telephone	Singapore 408868 65-6634 0600		
Fax	65-6634 0900		
Section 2	Composition and Ingredients		
<u>Components</u>	CAS No Approx. %		
Base Stocks	May include some or all of these: 80-95 68649-12-7, 68037-01-4, 64742-55-8 64742-54-7		
Proprietary ingredients	Mixtures which may include some or all of these:         8-21           25038-36-2,68648-42-3,63449-39-8         8-21		
Zinc or zinc compounds	May include 68649-42-3 0-2		
	The chemical identity of some or all of the above ingredients is confidential informatic and may be withheld as permitted under 29CFR 1910.1200. All the components of this material are listed on the TSCA Chemical Substances Inventory.		

Section 3	Hazards Identification	
Major route(s) of entry	Skin contact.	
Inhalation	No significant adverse health effects are expected to occur upon short-term exposure. At elevated temperatures, and/or in enclosed spaces, product mist or vapors may irritate the mucous membranes of the nose, throat, bronchi and lungs.	
Skin contact	This material can cause skin irritation from prolonged or repeated contact. Injection under the skin can cause inflammation and swelling. Injection of pressurised hydrocarbons can cause severe permanent tissue damage. Initial symptoms may be minor. Injection of petroleum hydrocarbons requires immediate medical attention.	
Eye contact	This product can cause transient mild eye irritation with short-term contact with liquid sprays or mists. Symptoms include stinging, watering, redness and swelling.	
Ingestion	If swallowed, large volumes of material can cause generalized depression, headache, drowsiness, nausea, vomiting and diarrhea. Smaller doses can cause a laxative effect. If aspirated into the lungs, liquid can cause lung damage.	
Chronic Health Effects Summary	This product contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at concentration above applicable work- place exposure levels can cause respiratory irritation or other pulmonary effects.	
Conditions aggravated	Disorders of the following organs or organ systems that may be aggravated	
by Exposure	by significant exposure to this material or its components include:	
Target Organs	This material may cause damage to the following organs:	
Carcinogen	This product is not known to contain any component at concentration above 0.1% which are considered carcinogenic by OSHA, IARC or NTP.	
Section 4 Eyes	<b>First Aid Measures</b> Check for and remove contact lenses. Flush eyes immediately with fresh water for several minutes while holding the eyelids open. If irritation persist,	
Skin	<ul> <li>see a doctor.</li> <li>If burned by hot material, cool skin by quenching with large amount of cold water.</li> <li>shoes and clothing. Wipe off excess material. Wash exposed skin with mild soap and water. Seek medical attention if tissue appears damaged or pain/ irritation persists. Thoroughly clean contaminated clothing before reuse. Discard contaminated leather goods. If material is injected under the skin, seek medical attention immediately.</li> </ul>	
Ingestion	Do not induce vomiting except on advice of medical personnel. Do not give anything to drink unless directed by a physician. Never give anything by mouth to a person who is not fully conscious. If significant amounts are swallowed or irritation or discomfort occurs, seek medical help immediately.	
Inhalation	Vaporization is not expected at ambient temperatures. This material is not expected to cause inhalation-related disorders under anticipated conditions of use. In case of overexposure, move the person to fresh air.	
Notes to Physician	Treatment should be controlled by symptoms and clinical conditions. Emesis maybe induced under medical supervision. In general, emesis induction is unnecessary in such high viscosity, low volatility product. SKIN: In the event of injection in underlying tissue, immediate treatment should include extensive incision, debridement, and saline irrigation. Inadequate treatment can result in ischemia and gangrene. Early symptoms maybe minimal.	

Section 5	Fire Fighting Measures	
Flammability	NFPA Class-IIIB combustible material	
Classification		
Auto Ignition Temp.	Not available	
Flammable limits	Not determined	
Flash Point, °C	> 200°C (COC)	
Extinguishing Media	Use water fog, dry chemical, foam or carbon dioxide type. Water or foam may cause frothing. Use water to cool fire-exposed containers. If a spill or leak has not ignited, use water spray to disperse the vapour and provide protection to personnel attempting to stop the leak.	
Explosion / Fire Hazards	For fires involving this material, do not enter any enclosed or confined space without self-contained breathing apparatus to protect against the hazardous effects of combustion products or oxygen deficiency.	
Hazardous Combustion Products	Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulphur and/or nitrogen.	
Section 6	Accidental Release Measures	
In case of Spill	Stop the source of leak or release and contain spill if possible. Ventilate the area. Use respirator and protective clothing as discussed in this MSDS. Collect with absorbent material and place in appropriate, labeled containers for disposal, or if permitted, flush spilled area with water.	
Section 7	Handling and Storage	
Handling	Avoid contamination and extreme temperatures to minimize product degradtion. Empty containers may contain product residues that can ignite with explosive force. Do not pressurize, cut, weld, braze, solder, drill or grind containers. Do not expose product containers to flames, spark, heat or other potential ignition sources.	
Storage	Keep containers closed. Do not store with strong oxidizing agents. Do not store at elevated temperatures. Avoid storing in direct sunlight for extended periods of time. Consult appropriate federal, state or local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product.	
Section 8	Exposure Controls / Personal Protection	
Ventilation	Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.	
Eyes	Avoid eye contact. The wearing of chemical safety goggles or face shield is recommended. Have suitable ear wash water available.	
Skin	Exposed personnel should exercise reasonable personal cleanliness; this includes cleansing exposed area several times daily with soap and water, and laundering or dry cleaning soiled work clothing at least weekly. Safety shower is recommended near the work station.	
Inhalation	Respiratory protection is normally not required. However, if operating conditions create airborne concentrations, which exceed the recommended exposure standard(s), the use of an approved respirator is recommended.	
Hand Protection	Use gloves of chemical resistant materials such as neoprene or heavy nitrile rubber or appropriate barrier cream with prolonged or repeated contact. If the product is processed or handled at elevated temperatures, protect against thermal burns by using heat-resistant (insulated) gloves. Do not wear gloves or loose fitting clothing around rotating or moving equipment.	
Clothing Recommendations	Long sleeve shirt is recommended. Wear a chemically protective apron if available. Do not wear rings, watches, or similar apparel that could entrap the material and cause a skin reaction.	

Exposure limits	Oil mist, mineral	ACGIH TLV (USA) TWA: 5 mg/m <sup>3</sup> 8 hrs STEL: 10 mg/m <sup>3</sup> 15 minutes	
		OSHA PEL (USA)	
		TWA: 5 mg/m <sup>3</sup> 8 hrs	
Section 9		cal Properties (Typical)	
SAE Grade	5W-30	5W-40	
Flash Point, <sup>°</sup> C	222	226	
Density @ 15°C, kg/l	0.853	0.852	
Viscosity@40°C, cSt	58.1	87.93	
Viscosity@100°C cSt	9.96	14.73	
Appearance	Amber		
Odour	Mild petroleum odour		
Boiling Range	Not determined		
Vapour Pressure	< 0.1 mmHg @ 25 deg C		
рН	Not determined		
Solubility in water	Insoluble		
Percent volatile	Negligible		
Evaporation	Not determined		
Section 10	Stability and Reactiv	vity	
Stability	Stable		
Conditions to avoid	Avoid heating to decomposition		
Incompatibility	Normally unreactive, however, avoid strong bases at high temperatures, strong acids, strong oxidising agents and materials reactive with hydroxyl compounds.		
Hazardous	No additional hazardous decomposition products were identified other than		
Decomposition products	the combustion products identified in Section 5.		
Hazardous polymerization	Will not occur		
Section 11	Toxicity Information		
Toxicity Data	Distillates, residue oils, petroleum light and heavy paraffinic:		
	ORAL (LD50) DERMAL (LD50)	Acute: > 5000 mg/kg [Rat]	
Primary routes of Entry or Exposure	DERMAL (LD50)Acute: > 2000 mg/kg [Rabbit]Skin absortion, eye contact and inhalation		
Inhalation		r mist is possible. High gas, vapor or mist concentration may ed repeatedly or for prolong periods of time, based on data similar products.	
Skin	Not expected to cause skin irritation or injury during normal use, based on toxicology tests of this product. Prolonged or repeated skin contact may cause skin irritation including redness, burning, drying, cracking, skin burns, dermatitis, oil acne and folliculitis based on data from components		
Еуе	Not expected to cause eye irritation or injury during normal use, based on toxicology tests of this product.		
Ingestion	Single dose toxicity is low, based on toxicology tests of this product		
		resiratory disorders may be aggravated by exposure,	
Acute Toxicity			

IATA Class	Not Restricted		
ADR/RID Class	Not Classified		
IMDG Marine Pollutant	No		
Classification	IMDG Class: not classified		
IMDG Code Shipping	Description: not regulated		
DOT Marine Pollutants	This product does not contain Marine Pollutants as defined in 49 CFR 171.8.		
	This product is not subjected to DOT regulations under 49 CFR Parts 171-180.		
	Labels Required: None		
Classification	UN Number: None		
US DOT Hazard	Proper Shipping Name: None		
Section 14	the time of disposal whether the material meets RCRA criterial for hazardou waste. This is because material uses, transformations, mixtures, processes etc may effect the classification. Transport Information		
Waste disposal	Check governmental regulations and local authorities for approved disposal Under RCRA, it is the responsibility of the user of the material to determine a		
Section 13	Disposal Information		
	eliminate natural atmospheric oxygen transport into the water. With time, in not removed, oxygen depletion in waterwaycan result in a loss of marine life of create an anaerobic environment.		
Environmental Fate	An environmental fate analysis has not been conducted on this specific product. Plants and animals may experience harmful or fatal effects when coated with petroleum-based produtcs. Petroleum-based (mineral) lube oils will normally float on water. In stagnant or slow flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit o		
Ecotoxicity	Analysis on ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal and aquatic life. Also the coating action associated with petroleum and petroleum products can be harmful or fatal to aquatic life and waterfowl.		
Section 12	Ecology Information		
	Good hygiene practices will reduce the likelihood of potential health effects		
	associated wth cancer in lifetime skin painting studies with laboratory animals. Avoid prolonged or repeated contact with used notor oil.		
	nausea, headache, unconsciouness, effects on hearing). Used engine oil was		
	central nervous system depression (dizziness, drowsiness, weakness, fatigue,		
	(nausea, vomiting, diarrhea), irritation (nose, throat, respiratory tract),		
Other information	Symptoms of overexposure could include: Gastrointestinal irritation		
	permanent nervous system damage.		
emonie roxieity	Reports have associated repeated and prolonged overexposure to solvents with		
Chronic Toxicity	No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.		
	exposure to liquids, vapors, mists or fumes should be minimised.		
	human health risks, which may vary from person to person. As a precaution,		

Section 16 None specified for this pro	Other Information	
RCRA Hazardous Class	Non hazardous	
Canadian DSL	All components are listed	
WHMIS (Canada)	Not regulated	
CERCLA	The Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning the release of quantities of "hazardous substances" equal to of greater than the Reportable Quantities (RQs) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. Chemical substances present in this product or refinery stream that may be subjected to this statute are: No components were identified.	
SARA 313 Toxic Chemical Notification and Release Reporting	This product may contain the following components in concentrations above de minimis levels that are listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements of Section 313 of SARA: No components were identified.	
SARA 311 / 312 Hazard Identification	The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this Subpart to submit aggregated information on chemicals by "Hazard Category" as defined in 40 CFR 370.2. This material is classified under the following hazard categories: No SARA 311/312 hazard categories identified.	
SARA 302 / 304 Emergency Planning and Notification	The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to emergency planning and notification information based on Threshold Planning Quantity (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.	
R Phrases	N/A N/A	
Labelling information	None needed	
Labelling information	Act (TSCA) Inventory.	
TSCA Inventory	This product and/or its components are listed on the Toxic Substances Control	
Respirator information	In the absence of local approval authorities/standards, follow US NIOSH/MSHA, UK BSI regulations. Respirators must meet the above or local standards for approved respirators	

While the data contained herein are believed to be factual, and the opinions expressed are those of qualified experts regarding the results of tests conducted, the data are not to be taken as a warranty or representation for which we assume responsibility. They are offered for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.