




# High Performance Gear Oils API GL-5



Fortified With  
**C60 Fullerenes**  
Technology

## **BARDAHL High Performance Gear Oils (API GL-5)** – SAE 80W-90

### **PRODUCT DESCRIPTION**

Bardahl Gear Oils (GL-5) are formulated with naturally high VI (viscosity index) paraffinic base stocks and sulphur-phosphorus additive system. These gear oils impart excellent oxidation stability characteristics and effective anti-weld, antiwear and anti-scuff properties. In addition, Bardahl Polar Plus technology with fullerenes provides enhanced protection to the gear systems.

### **C60 Fullerenes Technology**

Bardahl C60 Fullerene technology uses fullerene molecules to reduce friction and wear in engines. Fullerene molecules create a protective layer of hard particles on engine surfaces and prevent direct surface-to-surface contact. Being spherical in shape, C60 Fullerene molecules act as nano ball bearings, allowing surfaces to glide over one another with minimal friction and wear.

### **Advantages**

- High performance multipurpose gear lubricant
- Protects gears and bearings from wear at extreme pressures, and outstanding anti-wear protection
- Formulated to be compatible with “yellow metals” such as bronze found in synchronizers  
And other transmission components
- High temperature stability
- Inhibits foaming and aeration

### **Performance Standards**


API GL-5
----------

### **Applications**

- Suitable for the majority of automotive hypoid and spiral-bevel gear applications under high-speed/low torque or low speed/high torque in moderately severe load conditions.
- A excellent multipurpose extreme pressure lubricant for differentials and manual transmissions of passenger cars, trucks, vans, buses and off-road equipment that operates under mild to severe service conditions
- Designed for non-transmission gear boxes and steering boxes.
- Designed for applications requiring an API GL-5 specification.



# High Performance Gear Oils API GL-5



Fortified With  
**C60 Fullerenes**  
Technology

## Typical Properties

SAE GRADE	GL-5 SAE 80W-90
Appearance	Clear
Density, kg/litre@15°C	0.890
Kinematic Viscosity, mm <sup>2</sup> /s@40°C	148.0
Kinematic Viscosity, mm <sup>2</sup> /s@100°C	15.1
Viscosity Index	103
Pour Point, °C	-36
Flash Point COC, °C	218